

Standar Nasional Indonesia

Refined bleached deodorized oil

Note:

Translation without guarantee in the event of any doubt arising, the original standard in Indonesian is to be evidence

Based on the proposal of the Ministry of Trade this standard was approved by the Standardization Council of Indonesia - DSN to be the National Standard of Indonesia - SNI with the following number

SNI 01 - 0014 - 1987

CONTENTS

F	age
INTRODUCTION	1
SPECIFICATION	1
1. Scope	1
2. Description	1
3. Grades	1
4. Quality Requirements	1
5. Sampling	2
5.1 Method of Sampling	2
5.2 Sampling Official	2
6. Packing	2
6.1 Method of Packing	2
6.2 Labeling	2

REFINED BLEACHED DEODORIZED PALM OIL (RBD PALM OIL)

INTRODUCTION

The standard for Refined Bleached Deodorized Palm Oil was prepared, based on a survey conducted in the production centre for palm oil in North Sumatera, Lampung, DKI Jakarta and East Java.

After evaluation of the data and taking into consideration the Standards for RBD Palm Oil prepared by the the Palm Oil Research Institute of Malaysia (PORIM) the palm Oil Refiners Association of Malaysia (PORAM) and the standard proposed by the Staff of the Junior Minister Of Estate Products (Menteri Muda Urusan Peningkatan Produksi Tanaman Keras), the National Standard of Indonesia for RBD Palm Oil shall be as follows:

SPECIFICATION

1. Scope

This standard specifies the quality requirements, method of test, method of sampling and method of packing for Refined Bleached Deodorized Palm Oil (RBD Palm Oil).

2. Description

Refined Bleached Deodorized Palm Oil (RBD Palm Oil) shall be the oil obtained by the complete refining of the pericarp of the fruit Elaesis guineensis Jacq.

3. Grades

Refined Bleached Deodorized Palm. Oil shall be classified into one grade.

4. Quality Requirements

Characteristics		Requirements	Methods of test
-	Free Fatty Acid (as palmitic acid)% (w/w) max.	0.15	<u>SP - SMP - 30 - 1975</u> Rev. March 1984
-	Moisture and Impurities, % (w/w), max.	0.1	SNI 01 - 3184 - 1992
-	lodine value (Wijs) min.	50-55	SNI 01 - 3201 - 1992
-	Softening point °C min. max.	33 39	SNI 01 - 3191 - 1992
	Colour, Red/R max Yellow/Y max	30	SNI 01 - 3191 - 1992
-	Taste	normal*	Organoleptic

^{*)} Specific taste for RBD Palm Olein (Bland)

5. Sampling

5.1 Method of sampling

5.1.1 In bulk

a. Sampling from land tanks or other bulk containers. The sample shall be taken from the land tanks with a weighted bottle or metal container with a removable stopper to which is attached a chain or cord. It is lowered to the various recommended depths where the stopper is removed and the container allowed to fill. A Sample shall be taken from different depths (upper, middle and bottom). These samples are then mixed together. From this mixture 1 kg shall be taken for analysis.

b. Sampling from pipeline

The sample shall be taken from the outflow tap of the pipe through which the oil flows from the land tank to the ship. These samples are then mixed together and 1 kg shall be taken for analysis.

5.1.2 In drums

The sample shall be taken at random from the square root of the number of drums in a consignment with a maximum of 30 drums per consignment. The sample shall be taken from each drum with a valve sampling tube with a length of 125 cm and a diameter ± 2 cm. The orifice of the pipe can be closed or opened by a long stemmed plug.

By immersing this pipe into the drum, the oil shall be sampled from the upper layer down to the bottom layer. Samples shall be taken at four diagonally opposite corners and the four samples are then mixed together and from this mixture 1 kg shall be taken for analysis.

5.2 Sampling official

The sampling official shall be a person with experience or training and employed by a legal body.

6. Packing

6.1 Method of packing

Refined Bleached Deodorized Palm Oil shall be presented as a liquid, in bulk or packed in a drum which is in good condition clean and dry, with a capacity of 200 litres and a head space 5 - 10 percent. Drums for RBD Palm Oil should be made of a material which does not effect the contents and protects the product from contamination.

6.2 Labeling

On the outer surface of each drum, with non fading paint shall be written:

- Commodity of Indonesia
- Name/code number of producer/trader
- Name of commodity
- Net weight
- Code of production
- Country of destination
- Other important declaration



BADAN STANDARDISASI NASIONAL - BSN

Gedung Manggala Wanabakti Blok IV Lt. 3-4 Jl. Jend. Gatot Subroto, Senayan Jakarta 10270 Telp: 021- 574 7043; Faks: 021- 5747045; e-mail: bsn@bsn.go.id